

## AIR TOOLS

### LUBRICATORS

#### PORTABLE AIR LINE LUBRICATORS

Operate at full system pressure! Easy to install, it's adjustable oil feed and visible oil supply make these units ideal for portable or stationary tool applications.

With models ending in "C", the flow of the lubricant is continuous as long as the tool is operating. The other models inject a measured amount of lubricant each time the tool is started. Both types are fully adjustable, lightweight, rugged and suitable for all conditions.



PART NUMBER	3LUB8	6LUB12	8LUB12	16LUB16	16LUB16C*
Oil capacity (oz.)	3	5	8	16	16
NPT pipe size (in.)	1/2"	3/4"	3/4"	1"	1"
Max. air flow capacity @ 70 psi - 483 kPa (cfm)	30	45	80	200	200
Max. working pressure (psig)	300	250	300	250	250
Length (in.)	4 1/2"	6"	7"	10"	10"
Width (in.)	2 1/4"	2 3/4"	3 1/2"	4 1/4"	4 1/2"
Height (in.)	2 1/4"	2 3/4"	3 1/2"	3 3/4"	4 3/4"
Weight (lb.)	7/8	1 1/2	2	4 1/4	4 1/4

IN-LINE LUBRICATORS/INTERMITTENT FEED		
PRODUCT CODE	THREAD SIZE	AIR FLOW (CFM)
3LUB8	1/2" F X 1/2" F bsp	30
6LUB12	3/4" F X 3/4" F bsp	45
8LUB12	3/4" F X 3/4" F bsp	80
16LUB16	1" F X 1" F bsp	200